

ΠΙΝΑΚΑΣ ΕΠΙΛΟΓΗΣ ΣΤΟΜΙΩΝ LF-214, LF-214D

ΟΝΟΜΑΣΤΙΚΟ ΜΕΓΕΘΟΣ (mm)	Ak (m ²)	ΘΕΣΗ DAMPER	Q	750	1000	1250	1500	1750	2000	2500	3000	3500	4000	4500	5000
(600x600)	0,282		V	<1	1,1	1,3	1,5	1,7	2,0	2,5	3,1	3,6	4,0	4,5	5,0
		100% ΑΝΟΙΚΤΟ	ΔP	-	1,0	1,5	2,0	2,5	3,0	4,0	6,0	8,0	10,0	12,5	15,0
			Lα	-	<25	<25	<25	<25	<25	25	30	35	35	40	45
		50% ΑΝΟΙΚΤΟ	Δp	-	2,5	4,0	5,0	6,0	8,5	12,0	18,0	20,0	30,0	35	50
			Lα	-	<25	<25	25	25	30	35	40	45	50	>50	>50
		25% ΑΝΟΙΚΤΟ	ΔP	-	7,5	10,0	12,5	18,0	24,0	36,0	54,0	72,0	85,0	-	-
			Lα	-	<25	25	25	30	35	45	50	>50	>50	-	-

 Q: ΠΑΡΟΧΗ ΑΕΡΑ (m³/h)

ΔP: ΠΤΩΣΗ ΠΙΕΣΗΣ (Pa)

V: ΤΑΧΥΤΗΤΑ ΕΞΟΔΟΥ (m/s)

Lα: ΣΤΑΘΜΗ ΘΟΡΥΒΟΥ (dB(A))